

FISH LOCK

TECHNICAL SPECIFICATION

- Application: Control of Live sonar transducers
 - Product Code: FL17
 - Product weight: 3.5 kg
 - Origin: EU, Latvia, GDOG SIA
-

Control Unit

- Weight: 0.76 kg
 - Dimensions (L×W×H): 235 × 110 × 100 mm
 - Display diameter: 110 mm
 - Minimum supply voltage: 11 V
 - Maximum supply voltage: 32 V
 - Nominal current consumption at 12 V: 0.8 A
 - Maximum current consumption at 12 V: 3.5 A
 - Reverse polarity protection: Yes
 - Overheat protection: Yes
 - Power cable length: 2 m
 - Minimum rotation speed (360°/s): 4
 - Maximum rotation speed (360°/s): 29
 - Maximum rotation angle: 720°
 - Automatic operating modes: 2
 - Manual operating modes: 2
 - Gyroscope mode: Yes
 - Protection rating: IP65, UV-resistant surface
-

Transducer Lift & Mount System

- Dimensions (L×W×H): 185 × 210 × 70 mm
 - Weight: 2.55 kg
 - Transducer arm length: 0.95 m
 - Transducer arm diameter: 20 mm
-

Remote Control

- Dimensions (L×W×H): 45 × 25 × 26 mm
- Weight: 0.018 kg
- Battery: CR2032
- Current consumption (button pressed): 9.2 mA
- Current consumption (standby mode): 0.001 µA